



Product Specification

107 Technology Drive, Lincolnton, NC 28092 USA

info@activeconceptsllc.com • Phone: +1-704-276-7100 • Fax: +1-704-276-7101

Product Name: AC AmaraSense
Code Number: 12011
CAS #'s: 7732-18-5 & 84775-66-6 & 84082-82-6 & 84012-14-6 & & 1686112-36-6 (or) 68333-16-4 (or) 9015-54-7
EINECS #'s: 231-791-2 & 283-895-2 & 282-029-0 & 281-659-3 & & N/A (or) N/A (or) 295-635-5
INCI Name: Water & Glycyrrhiza Glabra (Licorice) Root Extract & Salix Alba (Willow) Bark Extract & Cynara Scolymus (Artichoke) Leaf Extract & Lactobacillus Ferment
Status: Conforms

Specification	Parameter
Appearance	Clear to Hazy Liquid
Color	Medium Amber to Brown
Odor	Characteristic
pH (Direct)	5.0 – 7.0
Refractive Index (25°C)	1.350 – 1.390
NVM (1g-1hr-105°C)	20.0 – 27.0%
Salicylic Acid	< 1 ppm
Tannic Acid	1.0% Maximum
Glycerrhethinic Acid	0.1% Maximum
Heavy Metals	< 20 ppm
Lead	< 10 ppm
Arsenic	< 2 ppm
Cadmium	< 1 ppm
Microbial Content	< 100 CFU/g; No pathogens
Yeast & Mold	< 100 CFU/g
Gram Negative Bacteria	0 CFU/g

Information contained in this technical literature is believed to be accurate and is offered in good faith for the benefit of the customer. The company, however, cannot assume any liability or risk involved in the use of its chemical products since the conditions of use are beyond our control. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent. We make no warranty of any kind, expressed or implied, other than that the material conforms to the applicable standard specification.



Product Specification

107 Technology Drive, Lincolnton, NC 28092 USA

info@activeconceptsllc.com • Phone: +1-704-276-7100 • Fax: +1-704-276-7101

May Sediment upon Standing; Mix Well Prior to Use

****Note:** Product may change appearance if exposed to cold temperatures during shipment or storage. If this happens, please gently warm to 45-50°C and mix until normal appearance is restored.

When handling this product please prevent exposure to temperatures above 25°C and prolonged exposure to UV. Exposure to temperatures above 25°C and direct UV may cause darkening.**

Information contained in this technical literature is believed to be accurate and is offered in good faith for the benefit of the customer. The company, however, cannot assume any liability or risk involved in the use of its chemical products since the conditions of use are beyond our control. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent. We make no warranty of any kind, expressed or implied, other than that the material conforms to the applicable standard specification.